



**SOLID COUNTERTOP SURFACES FOR LIFE.**

## Quartzstone Technical Specifications

### PRODUCT DETAIL

---

|                    |  |
|--------------------|--|
| Thickness Options  | 2CM / 3CM  |
| Standard Slab Size | 3200 x 1600 mm / Prefabricated options available |
| Color              | Metaform Color Library or Color Matched          |

### TEST DATA

---

|                                       |                  |   |
|---------------------------------------|------------------|---|
| Abrasion Resistance                   | EN 14617-4:2012  | 28.1mm                                      |
| Dimensional Stability                 | EN 14617-12:2012 | 0.03mm/Class A                              |
| Flexural Strength                     | EN 14617-2:2016  | 48.6MPa                                     |
| Impact Resistance                     | EN 14617-9:2005  | 2.57J                                       |
| Thermal Shock Resistance              | EN 14617-6:2012  | Change in flexural strength: 3.3%           |
| Slip Resistance                       | EN 14231:2003    | Dry: 48 / Wet: 7                            |
| Water Absorption and Apparent Density | EN 14617-1:2013  | Water Absorption:0.05% / Density: 2388kg/m3 |
| Chemical Resistance                   | EN 14617-10:2012 | C4  |
| Linear Thermal Expansion              | EN 14617-11:2005 | 20.4×10 <sup>-6</sup> /°C                   |

Visit [www.ascendcontract.com](http://www.ascendcontract.com) for more information.